

**Declaration of Performance**  
**No 01/2019/150/CL/E**

1. *Unique identification of product:* **Climateq PRO150 breathable membrane**
2. *Intended use:* **Breathable roof underlay CLIMATEQ is a flexible three-layer polypropylene sheet material for use as a roof tile underlays in warm non-ventilated, cold ventilated and cold non-ventilated pitched roof systems. It can be also used in timber-frame walls with a cavity and a masonry outer leaf, weatherboarding or tile/slate cladding. It is important that the designers, planners, contractors and/or installers ensure that the roof ceiling are constructed in accordance with the producer instructions and information.**
3. *Manufacturer:* **Z.P.H.U. WA-BIS Waldemar Wata, Łany 66, 28-330 Wodzisław, Poland**  
 Production plant: **Łany 66, 28-330 Wodzisław, Poland**
4. *System of assessment and verification of performance:* **System 3.**
5. *Harmonized standard covering the construction product:*  
**EN 13859-1:2010 Flexible sheets for waterproofing – Definitions and characteristics of underlays.**  
**Part 1: Underlays for discontinuous roofing**  
**EN 13859-2:2010 Flexible sheets for waterproofing. Part 2: Underlays for walls.**  
**Laboratory of Instytutu Mechanizacji Budownictwa i Górnictwa Skalnego Al. W. Korfanteo 193A, 40-157 Katowice, Notified body N° 1454)**
6. *Declared performances:*

ESSENTIAL CHARACTERISTICS	PERFORMANCES	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire [Class]	E	EN 13859-1:2010 EN 13859-2:2010
Resistance to water penetration before ageing [Class]	W1	
Tensile strength before ageing, [N/50mm]: - longitudinal - transverse	340 ± 60 210 ± 40	
Elongation before ageing, [%]: - longitudinal - transverse	60 ± 20 70 ± 20	
Tear resistance, [N]: - longitudinal - transverse	140 -45/+65 190 ± 65	
Flexibility at low temperature [°C]	-40	
Resistance to water penetration after ageing [Class]	W1	
Tensile strength after ageing, [N/50mm]: - longitudinal - transverse	290 ± 20 170 ± 20	
Elongation after ageing, [%]: - longitudinal - transverse	60 ± 15 70 ± 15	
Dangerous substances	Not contain	

The performance of the product identified in points 1 and 2 is in conformity with the declared performances in point 6.  
 This declaration of performance is issued based on the 305/2011 UE regulation under the sole responsibility of the manufacturer identified in point 3.

Łany 03.06.2019

Signed for on behalf of the manufacturer:  
**Waldemar Wata – President**

