

## Declaration of Performance N° 01/2019/210/CL/E

- 1. Unique identification of product: Climateq PRO210 FOCUS breathable membrane
- 2. Intended use: Breathable roof underlay CLIMATEQ is a flexible three-layer polypropylene sheet material for use as a roof tile underlays in warm non-ventilated, cold ventilated and cold non-ventilated pitched roof systems. It can be also used in timber-frame walls with a cavity and a mansonry outer leaf, weatherboarding or tile/slate cladding. It is important that the designers, planners, contractors and/or installers ensure that the roof ceiling are constructed in accordance with the producer instructions and information.
- 3. Manufacturer: Z.P.H.U. WA-BIS Waldemar Wata, Łany 66, 28-330 Wodzisław, Poland Production plant: Łany 66, 28-330 Wodzisław, Poland
- 4. System of assessment and verification of performance: System 3.
- 5. Harmonized standard covering the construction product:

EN 13859-1:2010 Flexible sheets for waterproofing – Definitions and characteristics of underlays.

Part 1: Underlays for discontinuous roofing

EN 13859-2:2010 Flexible sheets for waterproofing. Part 2: Underlays for walls.

Laboratory of Instytutu Mechanizacji Budownictwa i Górnictwa Skalnego Al. W. Korfantego 193A, 40-157 Katowice, Notified body N° 1454, Made the tests based on N°3 system

6. Declared performances:

ESSENTIAL CHARACTERISTICS	PERFORMANCES	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire [Class]	E	EN 13859-1:2010 EN 13859-2:2010
Resistance to water penetration before ageing [Class]	W1	
Tensile strength before ageing, [N/50mm]: - longitudinal - transverse	490 ±70 290 ±70	
Elongation before ageing, [%]: - longitudinal - transverse	60 ±25 70 ± 20	
Tear resistance, [N]: - longitudinal - transverse	230 ± 45 280 ± 45	
Flexibility at low temperature [°C]	-40	
Resistance to water penetration after ageing [Class]	W1	
Tensile strength after ageing, [N/50mm]: - longitudinal - transverse Elongation after ageing, [%]: - longitudinal - transverse	400 ± 20 225 ± 25 35 ± 10 45 ± 10	
Dangerous substances	Not contain	

The performance of the product identified in points 1 and 2 is in conformity with the declared performances in point 6. This declaration of performance is issued based on the 305/2011 UE regulation under the sole responsibility of the manufacturer identified in point 3.

Signed for on behalf of the manufacturer:

Waldemar Wata - President

Łany 03.06.2019